CodeMark

Certificate no: CMNZ70208
Version: 1
Original issue date: 19 June 2026
Version date: 26 October 2026

Product Certificate

Maxi-Butyl Flashing Tape

1. Certificate Holder Details

Marshall Innovations Ltd
384 Taurikura Drive, Omanawa 3171
Tauranga, New Zealand
admin@mwnz.com
Ph: 0800 776 9727
www.mwnz.com

2. Product Certification Body

Bureau Veritas Australia Pty Ltd
11/500 Collins Street
Melbourne VIC 3000 Australia
product.certification@bureauveritas.com
Ph: 1800 855 190
www.bureauveritas.com.au

Complaints: The complaints process for this certificate can be found here: www.bureauveritas.com.au/your-feedback

Sam Guindi – Bureau Veritas Product Certification Manager

3. Description of Building Method or Product

Name of the product or method in Aotearoa New Zealand, including any brand names used. Description of what it is and the components that make up any system and its physical attributes including the materials and make-up of the product, where applicable. Matters that should be taken into account in the use or application of the building method or product can be found in item 6. Conditions and Limitations of Use. Continuation of description can be found in item 10 – Supporting Information about Description. The building method's or building product's catalogue or model identification number or numbers or other unique identifiers that might be used to identify the building product or building method.

Maxi-Butyl Flashing Tape is a tear-resistant, UV-stable, pressure-sensitive flexible flashing tape manufactured from a butyl rubber copolymer. It is available in 75 mm, 150 mm, and 200 mm widths on 23 m rolls.

4. Intended use of Building Method or Product

Intended use of the building method or product as described in the product manual and other instructional materials. A statement of the function or purpose of the building method or product. Continuation of intended use can be found in item 11 – Supporting Information about Intended use.

Maxi-Butyl Flashing Tape is intended to be used as a self-adhesive flashing tape around window and door joinery openings as a secondary water-resistant barrier. It is used to seal junctions between framing and wall underlays, and to provide weather protection at sill, jamb, and head interfaces. The 75mm width may also be used to form corner "butterflies" and as a head flashing tape.

5. New Zealand Building Code Provisions

The performance clauses of the New Zealand Building Code that are relevant to the intended use and with which the building method or product complies or contributes to (where used as part of a system).
How the building method or product complies or contributes can be found in item 8. Basis for Certification. Any qualifications on the extent of that compliance can be found in item 6. Conditions and limitations of use.

B2 Durability: B2.3.1(a), B2.3.2(b)

E2 External Moisture: E2.3.2 (contributes to), E2.3.5 (contributes to), E2.3.6 (contributes to), E2.3.7 (contributes to)

F2 Hazardous building materials: F2.3.1

This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website https://tepae.building.govt.nz/public-registers/.

CodeMark

Product Certificate

Maxi-Butyl Flashing Tape

BUREAU VERITAS

Certificate no: CMNZ70208
Version: 1
Original issue date: 19 June 2026
Version date: 26 October 2026

6. Conditions and Limitations of Use

The building method or product's use is to be in accordance with the installation instructions and requirements against which the building method or product was assessed.
Conditions or limitations of conformity for the performance requirements the building method or product is compliant with, including any requirements for people with the qualifications and skills to install or use the building method or product, any known or demonstrated situations where the building method or product should not be used. A statement as to whether there are any matters that should be taken into account in the use or application of the building product or building method and, if so, what those matters are.

1. Maxi-Butyl Flashing Tape shall be used in buildings:
   a. within the scope of Acceptable Solution E2/AS1
   b. in wind zones up to and including Extra High, as defined in NZS 3604
   c. with wall underlays that meet the requirements of E2/AS1 and the Building Product Specifications.
2. Maxi-Butyl Flashing Tape shall be installed in accordance with Marshall Innovations' installation instructions and the WANZ Guide to Window Installation.
3. Maxi-Butyl Flashing Tape shall be covered within 180 days (6 months) of installation to limit exposure to ultraviolet radiation.
4. The compatibility of Maxi-Butyl Flashing Tape shall be confirmed with the substrate supplier when used over waterproofing membranes, coatings, rigid air barriers, and sealants. The substrate shall be clean, dry, and free from contaminants.
5. Maxi-Butyl Flashing Tape may be installed in temperatures between 0°C and 80°C, however cold substrates may reduce initial adhesion.
6. Maxi-Butyl Flashing Tape shall not be used in areas where it has the potential to be exposed to heat such as chimney flues.

7. Health and Safety Information

Health, safety, and well-being declarations associated with installation, maintenance, and use of the building method or product, and their specific editions and dates necessary to ensure the performance requirements of clauses F1 to F9 of the Building Code can be met.

The compliance with any manufacturer's installation instructions, maintenance, OH & S statements, MSDS's and other Health and Safety declarations will provide the necessary Health and Safety Information pertaining to the product.

8. Basis for Certification

How the performance requirements in the Building Code were met for each of the provisions. Where used as part of a system, the specific contribution to compliance.

B2 Durability - By testing and comparison with B2/VM1 using AAMA 711-20: Voluntary Specification for Self-Adhering Flashing and ASTM G154: For accelerated weathering/UV exposure.

E2 External Moisture - By testing and comparison with E2/AS1 using ASTM D3330 Method F: For peel adhesion, thermal cycling, accelerated aging and ASTM D1970: For tensile strength and water penetration resistance around fasteners and ASTM C765: For low-temperature flexibility.

F2 Hazardous building materials - By comparison with the performance requirements of F2.3.1.

JAS-ANZ

This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website https://tepae.building.govt.nz/public-registers/.

CodeMark

Product Certificate

Maxi-Butyl Flashing Tape

BUREAU VERITAS

Certificate no: CMNZ70208
Version: 1
Original issue date: 19 June 2026
Version date: 26 October 2026

9. Supporting Documentation for Certification

Reference to any acceptable solutions, verification methods, New Zealand Standards, or other compliance pathways referenced against each individual performance requirement the building method or product is compliant with, and their specific version and date. Reference to documents describing tests and evaluations and any other documents relied on for certification or used to prove compliance, including their full title, specific version and date.

1. Verification Method B2/VM1 Durability of buildings elements using in-service history, laboratory testing, and comparisons to similar materials, Third edition, 28 July 2025.
2. Acceptable Solution E2/AS1 External moisture provisions for timber-framed buildings up to 10 m in height, Fourth edition, 28 July 2025.
3. Acceptable Solutions and Verification Methods for New Zealand Building Code Clause F2 Hazardous building materials First edition (Amendment 3), 1 January 2017.
4. Building Product Specifications, First Edition, Amendment 1, 2 April 2026.
5. AAMA 711-20: Voluntary Specification for Self-Adhering Flashing.
6. ASTM D3330/D3330M-04, 2025; Standard Test Method for Peel Adhesion of Pressure-Sensitive Tape.
7. ASTM C765-97(2001) e1 Standard Test Method for Low-Temperature Flexibility of Preformed Tape Sealants.
8. ASTM D1970/D1970M-25 Standard Specification for Self-Adhering Polymer Modified Bituminous Sheet Materials Used as Steep Roofing Underlayment for Ice Dam Protection.
9. ASTM G154-23 Standard Practice for Operating Fluorescent Ultraviolet (UV) Lamp Apparatus for Exposure of Materials.
10. PRI Construction Materials Technologies LLC Laboratory Test Report, Project No. 2084T0012, March 28, 2022.
11. Maxi-Butyl Flashing Tape Install Guide, June 2024.
12. Maxi-Butyl Flashing Tape BPIR Declaration Version: Vn, 2 April 2026.
13. Material Safety Data Sheet - Article Information Sheet OHK-BUTYL-004, 20 June 2017.

JAS-ANZ

This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website https://tepae.building.govt.nz/public-registers/.

Product Certificate

Maxi-Butyl Flashing Tape

Certificate no: CMNZ70208
Version: 1
Original issue date: 19 June 2026
Version date: 26 October 2026

10. Supporting Information About Description (Optional)

Any supporting information for section 3.

N/A

11. Supporting Information About Intended Use (Optional)

Any supporting information for section 4.

N/A

12. Supporting Information About Conditions and Limitations of Use (Optional)

Any supporting information for section 6.

Only one layer of MAXI Butyl Flashing Tape required to the sill.

All CodeMark certificates that are current must be registered with MBIE. MBIE maintains a register of valid product certificates. Please find the register here.

If the certificate is not listed on this register or it appears as (SUSPENDED), it is not a valid CodeMark certificate and does not have to be accepted by a building consent authority as establishing compliance with the New Zealand Building Code.

This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website https://tepae.building.govt.nz/public-registers/.