



HYDRA Classic Wall Underlay

**Hydra
Classic**
WALL UNDERLAY

HYDRA Classic Wall underlay is a premium flexible synthetic underlay designed to be used behind exterior cladding systems.

It acts as a secondary weather-resistant barrier, protecting the building envelope from water ingress while allowing the safe passage of water vapour, contributing to a dry and durable wall assembly.



**Fire
Retardant**




Absorbent



**Water Vapour
Permeable**



UV 60 Days



25 | BUILDING ON
25 YEARS OF
INNOVATION
EST. NZ 1999

0800 776 9727
mwnz.com



Marshall
INNOVATIONS
CONSTRUCTION SOLUTIONS

Hydra

Classic

WALL UNDERLAY

Available in
1370mm x 37m
2740mm x 37m



Flame
Retardant



Absorbent



Water Vapour
Permeable



UV 60 Days

Scope

HYDRA Classic if designed, installed & maintained will meet or contribute to meeting the following provisions of the NZBC:

- Can be used with absorbent and non-absorbent claddings.
- Can be used with direct fix cladding and cavity applications.
- With masonry veneer in accordance with NZBC Acceptable Solutions E2/AS1 and E2/AS4.
- Can be used in all wind zones up to and including extra high when used with Rigid Air Barrier systems.
- Can be used as an air barrier in unlined spaces, such as attic spaces.

Storage

Store in a clean and dry area out of direct sunlight. Keep the rolls off the ground and don't store anything heavy on top of rolls

Product Code	Roll sizes	Coverage
HYCL1370	1370mm x 37m	50m ²
HYCL2740	2740mm x 37m	100m ²

Limitations

- Must not be exposed to UV for longer than 60 days.
- Insulation and internal linings cannot be installed until the exterior cladding is installed.

