

ProFoot:

- The new ProFoot offers greater versatility with 3 adjustable feet options starting at 30mm high with the ability to achieve heights of up to 700mm.
- Load bearing capacity 8.0kN



Adapters:

Select the appropriate adapter and simply click into the ProFoot head assembly.

The Stone Adapter is suitable for structural tiles or pavers. 4mm tabs provide consistent slab spacings

- 'L' Adapters suitable for side fixing aluminium sub-structure or timber joists.




Extension Rings:

- Two sizes of extension rings are available. 40mm & 100mm.
- Assembly heights of up to 700mm can be easily achieved with the extension ring options.



TradeWedge10:

- The new TradeWedge10, offers versatility with a base that will pivot from 0% to 10% in .5% degree increments to suit variable falls.
- A quick and easy installation solution that provides a stable base that doesn't move when you walk on it.
- Large supporting base.



TradePad:

- TradePad is a 10mm high EPDM disc to support timber, structural tiles or pavers.
- Consistent slab spacings provided by 4mm tabs.
- Reduces sound transmission.
- Tabs can be easily removed with a sharp knife.



TradeMat:

- 6mm rubber mat available as a 125mm x 125mm or a 250mm x 250mm.
- Reduces mechanical damage between membrane and pedestals.
- Eliminates known issues between plasticizers in membranes and pedestals.
- Reduces sound transmission.
- Other sizes available on request.

