



PRO-SILL SYSTEM

The professional's flexible flashing tape system for waterproofing window and door openings.



Protecto Tak Primer/Adhesive

369gm aerosol.

A spray on primer/adhesive coloured blue for easy identification.



Detail Tape

150mm x 15m rolls.

1mm thick comfortable tape that can be stretched and moulded to any shape



Protecto Sill

Polyethylene backed asphalt adhesive membrane 0.5mm thick.

Installation



Cut wall underlay and staple to inside of opening.



Apply Protecto Tak Primer to all areas that will be taped.



Cut detail tape to 250mm. Remove backing paper and fit to corners.



Peel plastic film from surface of Detail Tape and fold onto face of opening.



Detail Tape is required on all four corners of the opening. Press firmly into corners.



Cut Sill Tape 200mm long and apply to bottom of jamb and fold onto face of opening.



Cut Sill Tape to length, apply to sill and fold onto face of opening.



All tapes to be pressed firmly into place to maximise adhesion.

BENEFITS

- Slimline tapes that maximise opening space for window installation.
- Flexible flashing tape meeting E2 and WANZ requirements.
- Zero waste as tape can be overlapped.
- Primers allow adhesion to most substrates.
- 90 day UV stability.
- Can be used with RAB Systems. Primers give superior adhesion and can be exposed to UV for 90 days.

